

## V2-400G Test Module



With the rapid development of big data center, mobile Internet, Internet of Things and cloud computing services, as well as the widespread promotion and use of AR/VR/UHD video services and other technologies. The demand for data bandwidth in networked communication is increasing, and the arrival of 5G, with its ultra-high bandwidth, massive connections, low latency, and high reliability, is undoubtedly a powerful foundation for building all of this. In order to achieve ultra-high bandwidth of 5G, the increasingly 400GE technology in the backbone network and data center network of operators can further increase network capacity and reduce costs on the basis of 100GE, effectively solving the pressure brought by current business traffic and sustained growth of network broadband.

The V2-400G is new generation test module launched by Xinertel, which can meet the functional and performance test requirements of 400GE's network infrastructure and network equipment. It supports traffic and performance test scenarios including routers, switches, NICs, TAP switches, optical modules, DAC cables, etc.

### Key Features

- Native QSFP-DD 400G interfaces, compatible with 200GE/100GE
- Support L2-3 traffic generation and protocol emulation
- Support FPGA based 100% line rate traffic generation, statistics, and packet capture
- Support the benchmark test suites such as RFC2544, RFC2889, and RFC3918

### Models



**V2-400G-2QDD-Q test module**  
2-port 100G/200G/400G test module

## Specifications

| Hardware and electrical characteristics |   |
|---|---|
| Port speed                              | 400GE/200GE/100GE   |
| Port density                            | 2 ports   |
| Interface standards                     | 400G: 400GAUI-8(PAM4)<br>200G: 200GAUI-4(PAM4)<br>100G: CAUI-4(NRZ/PAM4)<br>400G FEC: 802.3-2018 CL119<br>200GFEC: 802.3-2018 CL119<br>100G FEC: 802.3-2018 CL91  |
| User reservation                        | Reservation by port   |
| Port speed switching                    | Switch the speed by port group(2 ports as a group)  |
| Weight(kg)                              | 1.7   |
| Dimensions (W x H x D)                  | 196mm x 35.5mm x 271mm  |
| Temperature                             | 0° C to 35° C   |
| Humidity                                | 20% to 85%  |
| Max power consumption(W)                | 133W  |
| Traffic generation                      |   |
| Max streams per port                    | 400G: 256; 200G: 256; 100G: 1024  |
| Frame length(byte)                      | 64-16383  |
| Frame length controls                   | Fixed, Increment, Decrement, Random, Auto, and IMIX   |
| Dynamic fields                          | 4 dynamic fields are available for each stream ; Support multiple dynamic controls such as Fixed, increment, Decrement, List, and Random.   |
| Transmit mode                           | Continuous, Burst, and Time Burst modes based on port; Continuous and Burst modes based on flow   |
| Bandwidth modification                  | Modify by port or flow  |
| Latency and jitter                      | LIFO, FIFO, LILO, and FILO  |
| Timestamp resolution                    | 8 nanoseconds   |
| Built-in protocol templates             | VLAN, ICMP, PPPoE, GRE, DHCP, L2TP, IPv6, MPLS, GTP, GOOSE, VXLAN, OSPF, TCP and UDP, etc.  |
| Customized frame                        | Support customizing the frame, and the edited frame template can be saved; Customized field can be checked with checksum.   |
| Customized payload                      | Support importing the 128K bytes customized payload and the first 128 bytes can be adjusted with jumping  |
| Statistics                              |   |
| Statistical streams per port            | 400G: 256; 200G: 256; 100G: 2048  |
| Statistical pattern                     | Csv statistics, chart statistics, automatic saving of csv files   |
| Statistics(Port)                        | Tx/Rx Frames, Tx/Rx Frame Rate, Rx Bandwidth, Error Frame Statistics, Filter Statistics, and Customized Statistics, FCS Error Statistics, TCP/UDP Checksum Errors, Pause Frame Statistics, etc.   |
| Statistics(Flow)                        | Tx/Rx Frames, Tx/Rx Flow rate, Rx Bandwidth, Error frame statistics, Real-time packet loss statistics, out of order statistics, delay, jitter and customized statistics, etc.   |
| Statistics operation                    | Support sorting of statistical results, performing mathematical operations such as addition, subtraction, multiplication, and division, and customizing the number of statistical entries for each page, etc.   |
| Protocol emulation                      |   |
| Routing and MPLS                        | RIPv1/v2, RIPng, OSPFv2/v3, BGP4/4+, ISISv4/v6, SR for BGP, BGP SR TE Policy, LDP, BGP VPLS   |
| Access                                  | PPPoE Client/Server, DHCPv4 Client/Server, DHCPv6 Client/Server, DHCPv4 Option 60, L2TPv2   |
| Multicast                               | IGMPv1/v2/v3, IGMP/MLD Querier, MLD, PIM, PPPoE over Multicast  |
| Data center                             | VXLAN IPv4/IPv6, VXLAN EVPN IPv4/IPv6, OpenFlow 1.3 Controller  |
| other                                   | BFDv4/v6, 802.1ag, 802.3ah, Y.1731  |
| Capture                                 |   |
| Capture buffer(Byte)                    | 32K   |
| Capture pattern                         | Capture of data and receive frames of the control plane; Capture of transmitted and received frames of the control plane; Capture based on filter templates; Capture filtered error packets; Capture buffer overwriting; Support specifying the number of downloaded capture packets. |
| Test suites                             |   |
| Benchmark test suite                    | RFC2544, Smart Scripter   |
| Software platform                       |   |
| Client software                         | RENIX   |
| API                                     | Tcl, Python3.x, GUIToTcl, GUIToPython   |
| GUI language                            | English, Simplified Chinese   |
| Hardware platform                       |   |
| Chassis                                 | BigTao220, BigTao6200   |
| Chassis operating system                | Linux CentOS7.X   |